

## TWO CHANNEL SET

**PRODUCT CODE: DW200HS-HET**



### Receiver's basic operation modes to be selected by user

- ON/OFF (bistable output mode)
- automatic OFF after programmed time (monostable output mode timing: from 0,25s up to 4 hrs)
- winch mode ( the receiver is ON for as long as keyfob is pressed)

### Receiver's Technical specification

- dynamic code system *KEELOQ®* of Microchip Corp. USA
- operating frequency: 433,92 MHz
- memory capacity: 104 keyfobs, at winch mode 20 keyfobs
- average range: 250m in open field
- power supply: 10..40 VDC or 13,5..29 VAC
- output relay ratings: 1A, 120VAC/30VDC
- number of channels/relay outputs: 2
- superheterodyne receiver module with sensitivity: -105 dBm,
- receiver's current consumption:
  - at 12VDC: 12 mA + 28 mA every relay set on,
  - at 24VDC: 6 mA + 14 mA every relay set on,
- operating temperature range from -20 to + 40 °C,
- signal output S (1A/60V max.) OC type,
- sabotage alarm terminals NC type (at box closed)
- external dimensions: (L/W/D) 96/63/28mm.

**Manufacturer:** ELMES ELEKTRONIK, 54-611 Wrocław, Avicenny 2, Poland

**Manufacturer's Limited Warranty:** 2 years